

DIAMOND *flexos*

Fiber Optic Passive Components

OUTLETS

With the FTTH surface mount socket you can bring in the fiber optics until your apartment. All communicative devices (data, phone, TV, etc.) can be transmitted over fiber optics.

The DIAMOND FTTH surface mount socket permits to splice easily up to four pigtailed with the fiber type G.657.A. The F-3000™ mating adapter and connector with laser- and dust protection flap are compatible with the current standard LC (IEC 61754-20/ED1).

FEATURES AND BENEFITS

- ▶ Easy mounting
- ▶ A sophisticated fiber management
- ▶ Separated 1m pigtail- and 1m cable reserve each
- ▶ Integrated Laser protection flaps in each centerpiece
- ▶ Simple assembly of an additional centerpiece
- ▶ Retainer for four Shrink- and Crimpsplice protections
- ▶ Individual dust protection flap on each centerpiece (blue circle; bottom picture)
- ▶ The Feller Edizio design provides a wide range of frame- and cover colors
- ▶ Overall dimensions (w x h x d in mm) 90 x 90 x 20

ORDER INFORMATION


PRODUCT NAME	DESCRIPTION	ORDER NUMBER
Surface mount socket	OSD 2/4 assembled with 2 pigtailed	EQE 1054930
Surface mount socket	OSD 4/4 assembled with 4 pigtailed	EQE 1054929
Pigtail set	1 pigtail red / 1 pigtail green, 1 mating adapter F3000™ APC (8°)	EQE 1054889
Upgrade set	1 pigtail yellow / 1 pigtail blue, 1 mating adapter F3000™ APC (8°)	EQE 1054937

FTTH Outlet

Outlet OSD2/4 + 4/4



Edizio
FELLER



DIAMOND SA • Via dei Patrizi 5 • CH-6616 Losone • Schweiz
Tel. +41 91 785 45 45 • Fax +41 91 785 45 00 • e-mail info@diamond-fo.com

www.diamond-fo.com

Specifications subject to change
without notice

BDD 1951147 079